


TR232 L

- Heavy duty guiding rail and tilting head facilitates precise cuts
- Built-in side extension accommodates large or wide materials
- Foldable handles, legs and transport wheels make moving and storing the machine simple
- The cutting table is easy to remove, which provides easy access to the water tray when cleaning
- Rubber coated table and clamps keep the cutting material steady and secure
- Ø 230mm Extreme Ceramic Turbo Diamond Blade supplied with every TR232 L



PRODUCT DATA

Item No.	70184601103	Supply Voltage / Power	230V 1~ / 1.1kW	Max. cutting depth at 90° / at 45°	15mm / 10mm
		Fuse/Generator	16A / 3 kVA	Max. cutting length	1200mm
		Blade x bore	Ø 230 x 25.4mm	Table size	1200 x 565mm
		Dimensions (LxWxH)	1860 x 600 x 1175mm	Tool speed RPM	2950 min ⁻¹
		Tilting head	0 - 45°	Hand Arm Vibrations	< 2.5 m/s ²
		Weight	72kg	Sound power / pressure level	71 dB (A) / 79 dB (A)



1200mm
MAX CUT LENGTH



PRODUCT FEATURES



ADJUSTABLE CLAMPS FOR FIXING THE TILES



ANGULAR CUTTING GUIDE / RUBBER-COVERED TABLE

DIAMOND BLADE WITH MACHINE FOR TR232 L



Substrate / Material	CERAMIC
Recommended Product	EXTREME CERAMIC TURBO
Blade x bore	230 x 25.4mm
Item No.	70184627653
Page reference	58